


MPF PRODUCTS INC.



A0485-6-BP





NOTE:

- 1. SHIELD: FLOATING
- 2. VOLTAGE: 2500 VOLTS DC SHIELD TO GROUND, 5000V PIN TO SHEILD
- 3. CURRENT: 5 AMPS
- 4. TEMPERATURE RATING: -200 TO 450°C (FEEDTHROUGH), 65 TO 165°C (AIRSIDE CONNECTOR)
- 5. IMPEDANCE: NON-CONSTANT

UNLESS OTHERWISE SPECIFIED: QUOTATION # N/A DIMENSIONS ARE IN INCHES DATE MPF PRODUCTS INC. TOLERANCES: DRAWN WJ 9/11/2015 9/11/2015 **TITLE:** CHECKED ANGULAR: MACH ± 1/2°
TWO PLACE DECIMAL ± .030
THREE PLACE DECIMAL ± .015 ENG APPR. WJ 9/11/2015 SHV-5 COAXIAL THIRD ANGLE: FEEDTHROUGH, 1 PIN, MATERIAL FLOATING SHIELD, 1" **BASEPLATE BOLT** DOWNLOADED FROM MPFPI.COM URFACE FINISH: DWG. NO. REV **FINISH** OR BETTER SHV A0485 UNLESS OTHERWISE SPECIFIED: PLATING ALL DIAMETERS CONCENTRIC WITHIN .00 Friday, January 18, 2019 8:56:32 AM SHEET 1 OF 1

SHV-5 Coaxial Feedthrough, 1 Pin, Floating Shield, 1" Baseplate Bolt, UHV Compatible

NO