


MPF PRODUCTS IN








AIR-SIDE CONNECTOR

VACUUM-SIDE CONNECTOR





SPECIFICATIONS:

- 1. TEMPERATURE RATING: -100 TO 450°C
- 2. LEAK RATE < 1X10-9 ATM CC/SEC HE

MS Series, Thermocouple Feedthrough, Type E, 3 Pairs, Double-Ended, w/ Air & Vacuum-side Connectors, 1.37" Dia Stainless Steel Weld Adpater

| UNLESS OTHERWISE SPECIFIED: | QUOTATION # | | | | | | |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------|------|-----------|-----------------------------------|--------------------------------------|---------|-----|
| | N/A | | | | | | |
| DIMENSIONS ARE IN INCHES TOLERANCES: | NAN | | DATE | MADE DOODLICTS INC | | | |
| | DRAWN | WJ | 9/11/2015 | MPF PRODUCTS INC | | | VC. |
| ANGULAR: MACH±1/2° TWO PLACE DECIMAL ± .030 | CHECKED | | 9/11/2015 | TITL | .E: | | |
| | ENG APPR. | WJ | 9/11/2015 | | | | |
| THREE PLACE DECIMAL ± .015 | THIRD ANGLE: | | | THERMOCOUPLE, TYPE E, | | | |
| | | | | 3 | PAIRS, MS CON | INFCT | OR. |
| MATERIAL | | | | DOUBLE ENDED, 1.372" WELD ADAPTER | | | |
| | | | | | | | |
| | APPLICATION NEXT ASSY USED ON | | | | | | |
| | | | | DOV | WNLOADED FROM M | PFPI.CO | Μ |
| FINISH | SURFACE FINIS | H: 6 | OR BETTER | DWC | G. NO. | | REV |
| PLATING | UNLESS OTHERWISE SPECIFIED: | | | A1093-1-W | | | |
| | ALL DIAMETERS CONCENTRIC WITHIN .005. REMOVE ALL BURRS AND SHARP EDGES | | | F | Friday, February 8, 2019 10:47:43 AM | | |
| DLE WITHOUT THE WRITTEN PERMISSION OF MPF PRODUCTS INC. IS PROHIBITED. SHEET 1 OF 1 | | | | | | | |