



MPF PRODUCTS INC.



PART #	# OF PINS	Ø "A"	"B"	"C"	BOLT CIRCLE	AIRSIDE CONNECTORS INCLUDED
A1600-1-QF	1	1.18	.3	2.5	OMIT	YES
A1600-2-QF	1	2.16	.4	2.4	OMIT	YES
A1600-3-QF	2	2.16	.4	2.4	.75	YES
A1600-4-QF	3	2.95	.4	2.4	.95	YES
A1600-5-QF	4	2.95	.4	2.4	.95	YES

NOTE:

1. SHIELD: GROUNDED
2. VOLTAGE: 10,000 VOLTS DC
3. CURRENT: 5 AMPS
4. TEMPERATURE RATING: -200 TO 450°C (FEEDTHROUGH), 65 TO 165°C (AIRSIDE CONNECTOR)
5. IMPEDANCE: NON-CONSTANT



SHV-10 Coaxial Feedthrough, 1/2/3/4 Pin, Grounded Shield, QF/KF, UHV Compatible

UNLESS OTHERWISE SPECIFIED:		QUOTATION #		N/A	
DIMENSIONS ARE IN INCHES TOLERANCES:		NAME	DATE	MPF PRODUCTS INC.	
ANGULAR: MACH ± 1/2°		DRAWN	WJ	9/11/2015	TITLE: SHV-10 COAXIAL FEEDTHROUGH, 1/2/3/4 PIN, GROUNDED SHIELD, QF/KF
TWO PLACE DECIMAL ± .030		CHECKED	WJ	9/11/2015	
THREE PLACE DECIMAL ± .015		ENG APPR.	WJ	9/11/2015	
MATERIAL		THIRD ANGLE:		DOWNLOADED FROM MPFPI.COM	
		APPLICATION		DWG. NO.	
		NEXT ASSY	USED ON	REV	
FINISH		SURFACE FINISH: 63/ OR BETTER		A1602	
PLATING		UNLESS OTHERWISE SPECIFIED:		Monday, January 21, 2019 11:16:13 AM	
		ALL DIAMETERS CONCENTRIC WITHIN .005. REMOVE ALL BURRS AND SHARP EDGES			