

## MPF PRODUCTS INC.





## SPECIFICATIONS:

- 1. MATERIAL: SAPPHIRE
- 2. TWD < 8λ @ 632nm (PEAK TO VALLEY)
- 3. PARALLELISM < 3 ARC-MINUTES
- 4. SURFACE FINISH: 50-20 SCRATCH-DIG 5. THERMAL RANGE: -100°C TO 450°C
- 6. ORIENTATION: RANDOM
- 7. LEAK RATE < 1X10-9 ATM CC/SEC HE

UNLESS OTHERWISE SPECIFIED: QUOTATION # N/A DIMENSIONS ARE IN INCHES NAME DATE MPF PRODUCTS INC TOLERANCES: DRAWN WJ 9/11/2015 9/11/2015 **TITLE:** CHECKED ANGULAR: MACH ± 1/2°
TWO PLACE DECIMAL ± .030
THREE PLACE DECIMAL ± .015 ENG APPR. WJ 9/11/2015 THIRD ANGLE: VIEWPORT, SAPPHIRE, UV, MATERIAL 3" VIEW, WELD ADAPTER APPLICATION NEXT ASSY DOWNLOADED FROM MPFPI.COM URFACE FINISH: DWG. NO. REV **FINISH** OR BETTER A1679-1-W UNLESS OTHERWISE SPECIFIED: PLATING ALL DIAMETERS CONCENTRIC WITHIN .003 Thursday, January 24, 2019 11:04:25 AM

SHEET 1 OF 1

UV Grade Sapphire Viewport, 2.95" View Dia, 3.50" Dia Stainless Steel Weld Adapter