




# MPF PRODUCTS INC.



PART #	CONDUCTOR MATERIAL	"A" DIM	CURRENT RATING
A2118-1-W	OFHC COPPER	0.094	30 AMPS
A2118-2-W	NICKEL 200	0.092	15 AMPS
A2118-3-W	304 STN STL	0.094	1 AMP

**NOTE:**

1. VOLTAGE: 5,000 VOLTS DC
2. CURRENT: SEE TABLE
3. TEMPERATURE RATING: -100 TO 450°C

Power Feedthrough W/ Power Glove, 5,000 Volts, 1 Pin, 0.435" Dia. Stainless Steel Weld Adapter, UHV Rated, Bakeable to 450°C

UNLESS OTHERWISE SPECIFIED:		QUOTATION #		N/A	
DIMENSIONS ARE IN INCHES TOLERANCES:		NAME	DATE	MPF PRODUCTS INC.	
ANGULAR: MACH ± 1/2"		DRAWN	9/11/2015		
TWO PLACE DECIMAL ± .030		CHECKED	9/11/2015		
THREE PLACE DECIMAL ± .015		ENG APPR.	9/11/2015		
MATERIAL		THIRD ANGLE:		TITLE: POWER GLOVE, 5000 VOLTS, 1 PIN, 0.435" WELD ADAPTER	
FINISH		APPLICATION			
PLATING		NEXT ASSY USED ON			
SURFACE FINISH: 63 OR BETTER		UNLESS OTHERWISE SPECIFIED:		DOWNLOADED FROM MPFPI.COM	
ALL DIAMETERS CONCENTRIC WITHIN .005. REMOVE ALL BURRS AND SHARP EDGES		DWG. NO.		REV	
		A2118		Tuesday, January 22, 2019 11:32:48 AM	