


## MPF PRODUCTS INC.



## SPECIFICATIONS:

1. OPERATING TEMPERATURE: 250°C
2. MULTICONDUCTOR RIBBON CABLE, 28 AWG
3. MULTI-STRAND CORE
4. 2 AMPS PER CONDUCTOR
5. VOLTAGE RATING: 600VAC, 2kVDC
6. NUMBER OF WIRES: 9
7. CABLE WIDTH: 0.41
8. CABLE THICKNESS: 0.05
9. INSULATION DIAMETER: .032
10. WIRE DIAMETER: 7 X 0.005
11. MINIMUM BEND RADIUS: 0.53

Subminiature D-type Connector/Connector, 9 Pins, In-Vacuum, Peek Connectors w/ Kapton Wire, 19" Length, Female Pins

UNLESS OTHERWISE SPECIFIED:	QUOTATION #		N/A
DIMENSIONS ARE IN INCHES	NAME	DATE	MPF PRODUCTS INC.
TOLERANCES:	DRAWN	9/11/2015	
ANGULAR: MACH ± 1/2°	CHECKED	9/11/2015	
TWO PLACE DECIMAL ± .030	ENG APPR.	9/11/2015	
THREE PLACE DECIMAL ± .015	THIRD ANGLE:		TITLE: CONNECTOR-CONNECTOR, TYPE-D, IN-VACUUM, 9 PINS, FEMALE, 19"
MATERIAL			
	APPLICATION		
	NEXT ASSY	USED ON	DOWNLOADED FROM MPFPI.COM
FINISH	SURFACE FINISH: 63/ OR BETTER		DWG. NO. A2370-1-CN
PLATING	UNLESS OTHERWISE SPECIFIED:		REV.
	ALL DIAMETERS CONCENTRIC WITHIN .005. REMOVE ALL BURRS AND SHARP EDGES		Wednesday, February 13, 2019 1:32:55 PM