


MPF PRODUCTS INC.







SPECIFICATIONS:

- 1. MATERIAL: CRYSTAL QUARTZ (Z-CUT)
- 2. TWD < 1λ @ 632NM (PEAK TO VALLEY)
- 3. PARALLELISM < 3 ARC MINUTES
- 4. SURFACE FINISH: 40/20 SCRATCH-DIG
- 5. THERMAL RANGE: -100 °C TO 200 °C
- 6. LEAK RATE < 1 X 10-9 ATM/CC SEC HE

UNLESS OTHERWISE SPECIFIED: QUOTATION # N/A DIMENSIONS ARE IN INCHES DATE MPF PRODUCTS INC TOLERANCES: DRAWN WJ 9/11/2015 9/11/2015 **TITLE:** CHECKED ANGULAR: MACH ± 1/2°
TWO PLACE DECIMAL ± .030
THREE PLACE DECIMAL ± .015 ENG APPR. WJ 9/11/2015 THIRD ANGLE: VIEWPORT, SIO2 VAC-MATERIAL OPTICS, 2" VIEW, 450CF NEXT ASSY DOWNLOADED FROM MPFPI.COM URFACE FINISH: DWG. NO. REV **FINISH** OR BETTER A4977-1-CF UNLESS OTHERWISE SPECIFIED: PLATING ALL DIAMETERS CONCENTRIC WITHIN .003 Thursday, January 24, 2019 11:18:57 AM

SHEET 1 OF 1

Crystal Quartz (SiO2) Viewport, UHV Rated Vacuum-Optics, 1.88" View Dia, 4.50" Conflat Flange