



PART NUMBER	"A" DIM	"B" DIM	NUMBER OF CONTACTS	CURRENT RATING (PER PIN)
A8275-1-CN	0.8	1.9	3	5 AMPS
A8275-2-CN	1.0	1.9	6	5 AMPS
A8275-3-CN	1.0	1.9	10	5 AMPS
A8275-4-CN	1.2	1.9	19	3 AMPS
A8275-5-CN	1.4	2.1	32	3 AMPS
A8275-6-CN	1.5	2.3	41	3 AMPS

SPECIFICATIONS: 1. TEMPERATURE RATING: UP TO 125°C

MS Series Air-side Connector, 1000 Volts

UNLESS OTHERWISE SPECIFIED:	QUOTATION #					
	N/A					
DIMENSIONS ARE IN INCHES		NAME	DATE		MPF PRODUCTS INC	
TOLERANCES:	DRAWN	W٦	9/11/2015	IV		
ANGULAR: MACH±1/2° TWO PLACE DECIMAL + .030	CHECKED		9/11/2015	TITL	TITLE:	
	ENG APPR.	WJ	9/11/2015			
THREE PLACE DECIMAL ± .015	THIRD ANGLE:			NAC CIDCLILAD CONNECTOD		
MATERIAL			MS CIRCULAR CONNECT		IUK,	
	APPLICATION NEXT ASSY USED ON					
	TIEM 7 00 T		0025 011	DOV	VNLOADED FROM MPFPI.CC	M
FINISH	SURFACE FINI:	SH: 6	OR BETTER	DWC	G. NO.	REV
PLATING	UNLESS OTHERWISE SPECIFIED:				A8275	
. 2	ALL DIAMETERS CONCENTRIC WITHIN .005. REMOVE ALL BURRS AND SHARP EDGES			Wednesday, January 13, 2021 2:18:51 PM		

SHEET 1 OF 1