



MPF PRODUCTS INC.

NOTES

1. CONFORMS TO MIL-DTL-83513/03
 - A. CONTACT PATTERN A THROUGH H
 - B. WIRE: ETFE COATED PER SAE-AS22759/33-26
COLOR CODED AS FOLLOWS, REPEATED EVERY 10 CONTACTS

1 - BLACK	6 - GREEN
2 - BROWN	7 - BLUE
3 - RED	8 - VIOLET
4 - ORANGE	9 - GREY
5 - YELLOW	10 - WHITE
 - C. SHELL: NICKEL PLATED ALUMINUM SHELL
 - D. MOUNTING HARDWARE: MIL-DTL-83513/05-02, CONFIGURATION A
(CONTACT PATTERNS A-G) OR MIL-DTL-83513/05-12 CONFIGURATION C (CONTACT PATTERN H)
2. ORDERING INSTRUCTIONS
SPECIFY BASE NUMBER FOLLOWED BY DASH NUMBER INDICATING PIN COUNT
EXAMPLE A9602 - 9 - 36

PART#	"A" DIM	"B" DIM
A9602-9-36	.795	.300
A9602-15-36	.945	.300
A9602-21-36	1.095	.300
A9602-25-36	1.195	.300
A9602-31-36	1.345	.300
A9602-37-36	1.495	.300
A9602-51-36	1.445	.343
A9602-100-36	2.056	.387



UNLESS OTHERWISE SPECIFIED:		QUOTATION #		APPROVED	
DIMENSIONS ARE IN INCHES TOLERANCES:		NAME	DATE	MPF PRODUCTS INC.	
ANGULAR: MACH ± 1/2°		DRAWN	11/19/2013		
TWO PLACE DECIMAL ± .030		CHECKED	11/19/2013		
THREE PLACE DECIMAL ± .015		ENG APPR.	11/19/2013		
MATERIAL		THIRD ANGLE:		CONNECTOR, MICRO-D NONHERMETIC PLUG	
		APPLICATION			
		NEXT ASSY USED ON			
FINISH		SURFACE FINISH:		DOWNLOADED FROM MPFPI.COM	
AIRSIDE CONNECTOR		63° OR BETTER			
PLATING		UNLESS OTHERWISE SPECIFIED:		DWG. NO. REV	
		ALL DIAMETERS CONCENTRIC WITHIN .005. REMOVE ALL BURRS AND SHARP EDGES		A9602	
				Thursday, February 14, 2019 10:52:51 AM	